

## FEDRA

## LED LAMP




## DETAILS

- Cameta™ lens technology
- Anti-glare lens
- CCT:  
5W: 2700K, 4000K, 6000K  
7W: 2700K, 4000K, 5000K
- Power factor: > 0.95
- CRI (Ra): 80...89
- Base: GU10
- Lifetime: 40.000 hrs
- Dimmable (7W)
- Non dimmable (5W)
- Very low energy consumption


## APPLICATIONS

- Spotighting for accents
- Display cabinets
- Shop windows
- Retail outlets
- Exhibition rooms
- Shops

FEDRA – 5W




FEDRA – 7W




Code	(W)	Base	CCT (K)	(lm)	Beam (°)	CRI (Ra)	a (mm)	h (mm)	Dim
LUX-L5W-24°-GU10-827	5	GU10	2700	350	24	80...89	∅ 50	70	No
LUX-L5W-24°-GU10-840	5	GU10	4000	375	24	80...89	∅ 50	70	No
LUX-L5W-24°-GU10-860	5	GU10	6000	390	24	80...89	∅ 50	70	No
LUX-L5W-38°-GU10-827	5	GU10	2700	350	38	80...89	∅ 50	70	No
LUX-L5W-38°-GU10-840	5	GU10	4000	375	38	80...89	∅ 50	70	No
LUX-L5W-38°-GU10-860	5	GU10	6000	390	38	80...89	∅ 50	70	No
LUX-L5W-60°-GU10-827	5	GU10	2700	350	60	80...89	∅ 50	70	No
LUX-L5W-60°-GU10-840	5	GU10	4000	375	60	80...89	∅ 50	70	No
LUX-L5W-60°-GU10-860	5	GU10	6000	390	60	80...89	∅ 50	70	No
LUX-L7W-24°-GU10-827	7	GU10	2700	550	24	80...89	∅ 50	88.5	Yes
LUX-L7W-24°-GU10-840	7	GU10	4000	570	24	80...89	∅ 50	88.5	Yes
LUX-L7W-24°-GU10-850	7	GU10	5000	600	24	80...89	∅ 50	88.5	Yes
LUX-L7W-38°-GU10-827	7	GU10	2700	550	38	80...89	∅ 50	88.5	Yes
LUX-L7W-38°-GU10-840	7	GU10	4000	570	38	80...89	∅ 50	88.5	Yes
LUX-L7W-38°-GU10-850	7	GU10	5000	600	38	80...89	∅ 50	88.5	Yes
LUX-L7W-60°-GU10-827	7	GU10	2700	550	60	80...89	∅ 50	88.5	Yes
LUX-L7W-60°-GU10-840	7	GU10	4000	570	60	80...89	∅ 50	88.5	Yes
LUX-L7W-60°-GU10-850	7	GU10	5000	600	60	80...89	∅ 50	88.5	Yes


5W – 2700K – 38°



5W – 6000K – 38°



7W – 4000K – 38°



7W – 5000K – 38°

