

# Villa LED series

## VILLA LED

## MULTIFACETED LED LAMP



### DETAILS


- Plastic base with brass bushing
- Surface Mount Devices (SMD)
- Diffusor: 8 faces with rigid LED and 1 frontal face
- CCT: 3000K, 4000K, 5000K
- Power factor: > 0.90
- CRI (Ra): 80...89
- 27W...54W: internal driver
- 60W...100W: external driver
- Protection: IP20, IP64
- Base: E27, E40
- Lifetime: 50.000 hrs

### APPLICATIONS

- Squares
- Parks
- Roads
- Factories
- Airports
- Subways
- Residential



### VILLA LED



Code	(W)	Base	CCT (K)	(lm)	LED n°	a (mm)	h1 (mm)	h (mm)	IP	Driver
LUX-VIL-L27W-E27-IP64-830	27	E27	3000	2.500	81	Ø 92,6	118	229	IP64	Internal
LUX-VIL-L27W-E40-IP64-830	27	E40	3000	2.500	81	Ø 92,6	118	229	IP64	Internal
LUX-VIL-L36W-E27-IP64-830	36	E27	3000	3.400	108	Ø 92,6	118	229	IP64	Internal
LUX-VIL-L36W-E40-IP64-830	36	E40	3000	3.400	108	Ø 92,6	118	229	IP64	Internal
LUX-VIL-L45W-E27-IP64-830	45	E27	3000	4.200	135	Ø 92,6	145	279	IP64	Internal
LUX-VIL-L45W-E40-IP64-830	45	E40	3000	4.200	135	Ø 92,6	145	279	IP64	Internal
LUX-VIL-L54W-E27-IP64-830	54	E27	3000	5.300	162	Ø 92,6	145	279	IP64	Internal
LUX-VIL-L54W-E40-IP64-830	54	E40	3000	5.300	162	Ø 92,6	145	279	IP64	Internal
LUX-VIL-L60W-E40-IP64-830	60	E40	3000	5.700	176	Ø 128	195	246	IP64	External
LUX-VIL-L80W-E40-IP64-830	80	E40	3000	7.600	220	Ø 128	195	290	IP64	External
LUX-VIL-L100W-E40-IP64-830	100	E40	3000	9.500	286	Ø 128	195	315	IP64	External

These codes refer to 3000K. Also available in 4000K and 5000K version.

These codes refer to IP64 protection class. Also available in IP20 version.

