

Maia series

MAIA

HIGH PERFORMANCE LED DOWNLIGHT



STANDARD COLOUR



DETAILS

- Adjustable tilt
- Aluminium mounting ring
- Aluminium die-cast heat sink with passive cooling
- Standard colours: white, grey
- Beam options: 28°, 40°, 60°
- CCT: 3000K, 4000K, 5000K
- Power factor: > 0.9
- CRI (Ra): 80...89
- Lifetime: 40.000 hrs
- Ta (°C): -30...40
- Supplied with LED driver
- Dimmable driver on request
- Mounting system through two quick-release springs

APPLICATIONS

- Shops
- Retail stores
- Hotels
- Halls
- Receptions
- Corridors
- Offices
- Common areas

FRAME OPTIONS

- Round, Ø 90: [R90]
- Round, Ø 110: [R110]





- Square, 90 × 90: [S90]
- Square, 110 × 110: [S110]



MAIA – R90 / R110

MAIA – S90 / S110



Code	(W)	CCT (K)	(lm)	Beam (°)	(mA)	CRI (Ra)	a (mm)	h (mm)	Cut-out	Shape
LUX-MAI-R90-L12W-40°-3K-[*]	12	3000	750	40	250	80...89	Ø 90	71	Ø 75	Round
LUX-MAI-R90-L12W-40°-4K-[*]	12	4000	800	40	250	80...89	Ø 90	71	Ø 75	Round
LUX-MAI-R90-L12W-40°-5K-[*]	12	5000	850	40	250	80...89	Ø 90	71	Ø 75	Round
LUX-MAI-R110-L12W-40°-3K-[*]	12	3000	750	40	250	80...89	Ø 110	71	Ø 75	Round
LUX-MAI-R110-L12W-40°-4K-[*]	12	4000	800	40	250	80...89	Ø 110	71	Ø 75	Round
LUX-MAI-R110-L12W-40°-5K-[*]	12	5000	850	40	250	80...89	Ø 110	71	Ø 75	Round
LUX-MAI-S90-L12W-40°-3K-[*]	12	3000	750	40	250	80...89	90	71	Ø 75	Square
LUX-MAI-S90-L12W-40°-4K-[*]	12	4000	800	40	250	80...89	90	71	Ø 75	Square
LUX-MAI-S90-L12W-40°-5K-[*]	12	5000	850	40	250	80...89	90	71	Ø 75	Square
LUX-MAI-S110-L12W-40°-3K-[*]	12	3000	750	40	250	80...89	110	71	Ø 75	Square
LUX-MAI-S110-L12W-40°-4K-[*]	12	4000	800	40	250	80...89	110	71	Ø 75	Square
LUX-MAI-S110-L12W-40°-5K-[*]	12	5000	850	40	250	80...89	110	71	Ø 75	Square

These codes refer to 40° beam option. Also available: 28°, 60° beam angles.

[* To complete the code, please choose the frame colour options: -W (white), -G (grey)].

12W – 40°

